




6 3/4" 172 mm Eliminator Drilling Motor 7-8 5.0 Stage



PHYSICAL DATA	STANDARD	METRIC
Motor OD	6.75"	172 mm
OD @ Stab Protector	7.55"	191.77 mm
Lobe Configuration	7-8 5.0 Stage	7-8 5.0 Stage
Overall Length	27.1'	8.26 m
Bit to Bend	6'	1.83 m
Bit to Stab Centre	1.6'	0.48 m
Weight	2607 lbs	1185 kg
Bit Size Range	8.5" - 9.88"	216 - 251 mm
Top Sub Connection	4.5xH, 4.5 H-90	4.5xH, 4.5 H-90
Bit Box Connection	4.5" Reg	4.5" Reg
Adjustable Range	0-3 Degree	0-3 Degree
PERFORMANCE DATA	STANDARD	METRIC
Flow Range	300 - 600 gpm	1125 - 2250 Lpm
Revolutions per	0.28/gal	0.075/L
Max Bit Speed	85 - 170 rpm	85 - 170 rpm
Max Operating dP	600 psi	4143 kPa
Operating Torque	6000 ft-lbs	8150 Nm
Horsepower	194 hp	145 kW
WOB, Operating	22,000 lbs	9800 dN
Maximum Allowable Pull	200,000 lbs	89,000 dN

