




## 9 5/8" 244 mm Eliminator Drilling Motor 5-6 5.0 Stage



PHYSICAL DATA	STANDARD	METRIC
Motor OD	9.63"	244 mm
OD @ Stab Protector	10.6"	269.24 mm
Lobe Configuration	7-8 5.0 Stage	7-8 5.0 Stage
Overall Length	29.3'	9 m
Bit to Bend	7'	2.13 m
Bit to Stab Centre	2'	0.6 m
Weight	5192 lbs	2360 kg
Bit Size Range	12.25" - 17.5"	311 - 445 mm
Top Sub Connection	6.63" Reg	6.63" Reg
Bit Box Connection	6.63" Reg	6.63" Reg
Adjustable Range	0-3 Degree	0-3 Degree
PERFORMANCE DATA	STANDARD	METRIC
Flow Range	600 - 1000 gpm	2500 - 3750 Lpm
Revolutions per	0.18/gal	0.05/L
Max Bit Speed	110 - 180 rpm	110 - 180 rpm
Max Operating dP	600 psi	4140 kPa
Operating Torque	10,500 ft-lbs	14,250 Nm
Horsepower	360 hp	270 kW
WOB, Operating	46,200 lbs	20,580 dN
Maximum Allowable Pull	375,000 lbs	167,000 dN

